



Hitouch 5N

HN18N-78HT

625-650W

BIFACIAL

High Efficiency Module

23.3%

Maximum Efficiency



Long-Term Reliability

Module certified to withstand 5400 Pa positive static load and 2400 Pa negative static load.

Excellent anti-PID performance to guarantee a better sustainability in harsh environment.



Lower Hot Spot and Crack Risk

Reduce hot-spot risk with optimized electrical design and lower operating current.

Reduce crack risk by MBB solar cell design.



Higher Power Output

Higher module conversion efficiency benefit from bigger wafer and half-cell structure.


MBB technology enhances current collection with lower series resistance.



Excellent Temperature Coefficient

Lower operating temperature and temperature coefficient increases the power output.

Power Warranty



Certificates



Warranty partner

Munich RE

About Hanersun

Hanersun is a world-leading clean energy company, focusing on R&D, manufacturing and distribution of solar module and energy storage system, as well as comprehensive clean energy solutions. Committed to high-efficiency technologies, the company is one of the first to launch PV modules of 600W+ and 700W+ in the industry.

Electrical Characteristics (STC)

Module Type	HN18N-78HT625W	HN18N-78HT630W	HN18N-78HT635W	HN18N-78HT640W	HN18N-78HT645W	HN18N-78HT650W
Maximum Power (Pmax)	625	630	635	640	645	650
Maximum Power Voltage (Vmp)	46.58	46.78	46.98	47.18	47.38	47.58
Maximum Power Current (Imp)	13.42	13.47	13.52	13.57	13.62	13.67
Open-circuit Voltage (Voc)	55.80	56.00	56.20	56.40	56.60	56.80
Short-circuit Current (Isc)	14.22	14.26	14.30	14.34	14.38	14.42
Module Efficiency(%)	22.4%	22.5%	22.7%	22.9%	23.1%	23.3%

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5.

Power Tolerance: 0~+3%

Electrical Characteristics (BNPI)

Module Type	625W	630W	635W	640W	645W	650W
Maximum Power (Pmax)	693	698	704	709	715	721
Maximum Power Voltage (Vmp)	46.58	46.78	46.98	47.18	47.38	47.58
Maximum Power Current (Imp)	14.88	14.93	14.99	15.03	15.10	15.16
Open-circuit Voltage (Voc)	55.80	56.00	56.20	56.40	56.60	56.80
Short-circuit Current (Isc)	15.76	15.80	15.84	15.89	15.93	15.98

BNPI: Irradiance: Front 1000W/m², Rear 135W/m², Cell Temperature 25°C, Air Mass AM1.5.

Mechanical Parameters

Solar Cells	N-TYPE Monocrystalline(182mm)	No. of Cells	156 [2 x (13 x 6)]
Module Dimensions	2465*1134*30mm	Weight	32.8kg
Glass	2mm-2mm	J-Box	IP68
Frame	Anodized Aluminium Alloy	Connector	Z4S-abcd/MC4-EVO 2A/Others
Output Cable	4.0mm²	Cable Length	300/300mm (can be customized)

Operating Parameters

Operational Temperature	-40°C~+70°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	30A
Bifacility	80±5%
Fire Class Rating	Class C


Packaging

Pcs per Pallet: 37



Temperature Ratings

Temperature Coefficient of Pmax	-0.28%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Isc	+0.045%/°C

Dimensions (Unit: mm)




Front View



Back View

I-V Curves of PV Module (630W)



P-V Curves of PV Module (630W)

