

HNB-LV

Wall Mounted Energy Storage Battery

5/10 kWh



KEY FEATURES



Support 1-8 battery in parallel.

Safe & Reliable

Lithium iron phosphate(LFP) cell. Built-in BMS &Passive protection by fuse and aerosol.

Easy Installation

Reduce floor space. Wall-mounted or floor-mounted is selected freely.

Environmental Adaptability

Wide range of temperature: -10°C-55°C. IP 65 ingress protection.

Perfect Compatibility

Compatible with residential single phase inverters.

Long Life Span

15-20 years life design, more than 6000 cycles.

© 2023 HANERSUN ESS Solution Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.



PRODUCT PARAMETER

Electrical Characteristics

Model	HNB5K-LV	HNB10K-LV
Nominal Capacity	5.22kWh	10.44kWh
Voltage	51.2V	51.2V
Charge Voltage	57.6V	57.6V
Discharge Voltage Range	43.2-57.6V	43.2-57.6V
Max. Charging Current	40A	90A
Max. Discharging Current	75A	140A
Battery Type	LiFePO4	LiFePO4
Max. Output Power	3840W	7168W
DOD	90%	90%
Modules Connection	1-8 in parallel	1-8 in parallel
Communication	CAN OR RS485	CAN OR RS485
Cycle Life	≥6000 25°C 0.5C	≥6000 25°C 0.5C

Operating Conditions

Working Temp Range	Charge: 0°C-+55°C, Discharge: -10°C-+55°C	
Storage Temperature(°C)	-20°C-+35°C	
Net Weight (kg)	48.5kg	96kg
Gross Weight (kg)	52.5kg	125kg
Product Dimension (mm)	536.3*464*180.5	790*586*197
Package Dimension (mm)	592*522*252	950* 720*390

CERTIFICATES



WARRANTY

5 YEARS

© 2023 HANERSUN ESS Solution Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Tel: +86-25-52791766 Email: sales@hanersun.com

Website: www.hanersun.com